



1-1. HOUSING & CONTACT ASSEMBLY

1. MATERIAL:
 - 1-1. HOUSING: PBT, UL94V-0
CONTACT: COPPER ALLOY.
 - 1-2. PLASTIC COVER: ABS
 - 1-3. METAL SHELL: COPPER ALLOY, NICKEL PLATED.
 - 1-4. METAL CAP: COPPER ALLOY, NICKEL PLATED.
 - 1-5. CABLE FIXER: COPPER ALLOY, TIN PLATED.
 - 1-6. POM RING: POM
 - 1-7. SPRING: STEEL, NICKEL PLATED.
 - 1-8. PLASTIC TUBE: ABS
 - 1-9. SR: PVC
2. FINISH:
 - 2-1. CONTACT: SILVER 50u"
3. ELECTRICAL SPECIFICATION :
 - 3-1. RATED CURRENT : 7.5A/DC MAX
 - 3-2. RATED VOLTAGE : 20V/DC MAX
4. ENVIRONMENTAL :
 - 4-1. OPERATION TEMPERATURE : -20 ℃~85℃

7.0
6.5
5.5
5.0
4.0
SR OD

RoHS Compliant			
APPD 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 ±0.10 ±0.05 ±0.03 ±0.02 ±0.01 ±0.005 ±0.0025 ±0.00125	PART NAME 品名 4P QUICK LOCK POWER PLUG ASSEMBLY TYPE CONTACT PLATING: SILVER ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 PC-MDP-402-4P
DATE 製表日 2012/10/16	PAGE 張數 1 OF 1	REV. 版次 A	